## **Product Information**

### **AVENO Ultra 20W-50**

0002-000314



#### Description

AVENO Ultra 20W-50 is an engine oil on mineral oil basis with selected additives for demanding petrol engines from 2001 and later, and 4-stroke motorbikes. AVENO Ultra 20W-50 has excellent lubricating film adhesion and good shear stability, as well as outstanding cleaning capability and high resistance to aging.

#### Instructions for use

AVENO Ultra 20W-50 is intended for the typical operation of petrol engines in current and earlier (from 2001 onwards) cars, sport utility vehicles, vans and light trucks during maintenance measures recommended by vehicle manufacturers. Oils that meet the API SL requirements can be used wherever the API service category SJ and earlier categories are recommended. AVENO Ultra 20W-50 is also excellently suited as engine oil for motorbikes, when the specification SAE 20W-50 JASO MA/MA2 is required.

# Quality classification Specification

• API SL • JASO MA-2

#### **Properties**

Technical specifications			
Properties	Data	Unit	Testing under
Kinematic Viscosity at 100°C	19.1	mm²/s	DIN ISO 51562-2:1988-12
Viscosity Index	122		DIN ISO 2909:2004-08
Appearance	YELLOW		VISUELL
Density at 15°C	883	kg/m³	DIN EN ISO 12185:1997-11
Pour Point	-30	°C	ASTM D 7346:2015