Product Information

AVENO MotorCycle 4 Stroke FS 15W-50

0002-000364



Description

AVENO MotorCycle 4 Stroke FS 15W-50 is a synthetic high-performance, smooth-running engine oil for demanding 4-stroke motorbikes. It allows for fuel-saving engine operation and low levels of evaporation. AVENO MotorCycle 4 Stroke FS 15W-50 is characterised by its excellent cold starting properties, as it ensures optimum lubrication reliability during the cold-running phase.

Instructions for use

AVENO MotorCycle 4 Stroke FS 15W-50 is especially suitable as a high-performance, smooth-running engine oil for all motorcycles, when the specification SAE 15W-50 is required. AVENO MotorCycle 4 Stroke FS 15W-50 meets the high-tech demands of the latest high-performance engine generation. For professional racing we recommend our racing products.

Quality classification			
Specification			
• API SL		• JASO MA2	
Properties			
Technical specifications			
Properties	Data	Unit	Testing under
Kinematic Viscosity at 40°C	125.0	mm²/s	DIN ISO 51562-2:1988-12
Kinematic Viscosity at 100°C	17.5	mm²/s	DIN ISO 51562-2:1988-12
Viscosity Index	155		DIN ISO 2909:2004-08
Appearance	YELLOWBROWN		VISUELL
Density at 15°C	869	kg/m³	DIN EN ISO 12185:1997-11
Pour Point	-36	°C	ASTM D 7346:2015

Notice: To the best of our knowledge, all of the information provided was in accordance with the latest findings and developments of the Deutsche Ölwerke Lubmin GmbH. Our products are subject to continuous development. For this reason, our products, the manufacturing processes and all related information on this product page are subject to change at any time and without notice, unless customer-specific agreements exist. The data listed are based on standardized test procedures under appropriate laboratory conditions and are to be regarded as general, non-binding reference values.