

Product Information

AVENO Low Emission Diesel 10W-30

0002-000647



Description

AVENO Low Emission Diesel 10W-30 is a high quality truck engine oil formulated with Low SAPS technology. It can be used in both older and new engines. AVENO Low Emission Diesel 10W-30 improves engine performance, reliability and cleanliness engines. It reduces fuel consumption and wear as it reduces friction.

Instructions for use

AVENO Low Emission Diesel 10W-30 is most suitable in Euro 6 engines with exhaust systems and in Euro 3, 4, 5 engines when specified by the engine manufacturer.

Quality classification			
Specification			
• API CK-4/SN		• ACEA E6/E7/E8/E9/E11	
Recommendation			
• Caterpillar ECF-3		• DTFR 15C110 (228.51)	
• Cummins CES 20081/20086		• MAN M 3477	
• DDC 93K222, DDC 93K218		• MTU Typ 3.1	
• Deutz DQC IV-10 LA		• Renault VI RLD-4	
• Mack EOS-4.5		• VOLVO VDS-4.5	
Properties			
• Stable viscosity behavior		• Very good wear and corrosion protection	
• Protection against sludging, coking & varnishing		• High oxidation stability & engine cleanliness	
• Excellent detergent & dispersant properties			
Technical specifications			
Properties	Data	Unit	Testing under
Kinematic Viscosity at 40°C	79.6	mm²/s	DIN 51659-2:2017-02
Kinematic Viscosity at 100°C	12.2	mm²/s	DIN 51659-2:2017-02
Viscosity Index	150		DIN ISO 2909:2004-08
Appearance	YELLOWBROWN		VISUELL
Density at 15°C	860	kg/m³	DIN EN ISO 12185:1997-11
Pour Point	-36	°C	ASTM D 7346:2015