## **Product Information**

### **AVENO MBike 20W-40**

0002-000711



#### Description

AVENO MBike 20W-40 is a motor oil based on hydrocrack oils with selected additives for demanding 4-stroke motorcycles. It is characterized by high resilience and reliabilityand is specially designed for wet and oil-lubricated clutches. AVENO MBike 20W-40 has excellent lubricating film adhesion, good shearing stability, excellent cleaning power andhigh aging resistance.

#### Instructions for use

AVENO MBike 20W-40 eignet sich als Motorenöl für alle Motorräder, wenn die Spezifikation SAE 20W-40 gefordert wird.

# Quality classification Specification • API SN • JASO MA2

| Pro | n۵ | т | ΔC |
|-----|----|---|----|
| Pro | 2  |   | 5  |

- Excellent cold start properties
- · High oxidation stability
- Prevention of black sludge formation

- Outstanding shear stability
- Very good detergent and dispersing properties
- Very good viscosity-temperature behaviorcatalyst suitability

| Technical specifications     |             |         |                          |  |
|------------------------------|-------------|---------|--------------------------|--|
| Properties                   | Data        | Unit    | Testing under            |  |
| Kinematic Viscosity at 40°C  | 124.9       | mm²/s   | DIN 51659-2:2017-02      |  |
| Kinematic Viscosity at 100°C | 14.2        | mm²/s   | DIN 51659-2:2017-02      |  |
| Viscosity Index              | 113         |         | DIN ISO 2909:2004-08     |  |
| Appearance                   | YELLOWBROWN |         | VISUELL                  |  |
| Density at 15°C              | 875         | kg/m³   | DIN EN ISO 12185:1997-11 |  |
| Pour Point                   | -39         | °C      | ASTM D 7346:2015         |  |
| Total Base Number (TBN)      | 7.9         | mgKOH/g | ASTM D 2896:2021         |  |