# **Product Information**

## **AVENO LL Motion 12FE 0W-30**

### 0002-001101



### Description

AVENO LL Motion 12FE 0W-30 is a synthetic smooth-running engine oil for petrol and diesel car engines of light transporters and high-performance vehicles with or without turbocharger and direct injection. AVENO LL Motion 12FE 0W-30 guarantees a high operational reliability in all driving conditions such as extreme stop-and-go-traffic as well as high-speed motorway driving.

### Instructions for use

AVENO LL Motion 12FE 0W-30 is an energy efficient engine oil for year-round use, and can be used in modern petrol and diesel car engines. AVENO LL Motion 12FE 0W-30 is suitable for extended oil change intervals and extends the lifespan of the particulate filter. The operating instructions of the automobile and engine manufacturer must be observed.

Quality classification		
Specification		
• ACEA A5/B5	• API SP (RC)	
• ACEA C2	• ILSAC GF-6	
Recommendation		
• BMW Longlife-12 FE	• Ford WSS-M2C950-A	
• MB 227.61, 229.61	• VWC 53035	
Properties		

- Long lifespan due to high oxidation stability
- Prevents black sludge from forming
- Low evaporation, thus low oil consumption
- Suitable for catalytic converters

- A very stable and excellent viscosity behavior and shear stability
- Fuel savings due to smooth-running characteristics
- Excellent protection against wear, corrosion and foaming
- Extended oil change intervals protect natural resources

Technical specifications				
Properties	Data	Unit	Testing under	
Kinematic Viscosity at 40°C	55.3	mm²/s	DIN 51659-2:2017-02	
Kinematic Viscosity at 100°C	10.2	mm²/s	DIN 51659-2:2017-02	
Viscosity Index	174		DIN ISO 2909:2004-08	
Appearance	BROWN		VISUELL	
Density at 15°C	844	kg/m³	DIN EN ISO 12185:1997-11	
Pour Point	-48	°C	ASTM D 7346:2015	